

TECHNICAL SPECIFICATIONS

GENERAL INFO

Birds per meter trough	13 - 15
Cm of trough per bird	13,3 - 15,4

GENERAL & TECHNICAL INFO

Drive unit	0,37 kW - 1/2 HP 3 phase 50 Hz 84 RPM
Capacity per feed intake boot (*)	700 kg/hour
Maximum auger length - circuit with 1 motor	80 m
- circuit with 2 motors	200 m
- circuit with 3 motors	300 m
- circuit with 4 motors	400 m
Roller tube: height adjustment	from 40 to 50 mm (11 positions)
FIXGRILL™	45 mm width x 65 mm height
Suspension points	every 3 m
Average height	3,25 m
Max. pellet diameter	4 mm

(*) Based on a specific weight of 0,65 kg/dm³!

BRIDOMAT™ is an exclusive
Roxell®-product.

ROXELL® reserves the right to make modifications to improve its products
or systems, without prior notification.

Your ROXELL® Service Point:

00704734 - ©ROXELL® NV - 05/2011 - Leaflet BRIDOMAT™ English



BRIDOMAT™

**Trough feeding system
for broiler breeders**

ROXELL®

ROXELL® NV Belgium - Industrielaan 13 - 9990 Maldegem,

Tel. +32 50 72 91 72 - Fax +32 50 71 67 21 - E-mail: roxell@roxell.com - www.roxell.com

ROXELL® Millenium House - 5th Floor, Ul. Trubnaya 12, 107045 Moscow, Russian Federation

Tel: +7 495 795 0657 - Fax: +7 495 795 0632 - Email: info.russia@roxell.com - www.roxell.ru

ROXELL® Malaysia - No. 12 Jalan Anggerik Mokara 31/48, Kota Kemuning Industrial Park,

40460 Shah Alam, Selangor, Malaysia - Tel: +603-5121 7150 - Fax: +603-5121 7146

Email: info@roxell.com.my - www.roxell.com.my

ROXELL®



BRIDOMAT™

1

Excellent uniformity

- Uniform feed distribution in equal portions all over the circuits.
- A high transport capacity (30m per minute) to exclude eating during the feed distribution.
- No selective pecking, no piling up of feed. All birds have equal chances.

2

Important feed savings

- Special trough shape to exclude feed waste.
- The auger divides the trough into thousands of small feed compartments, thus protecting the feed.
- Handy feed level adjustment disc on the feed intake boot.

BRIDOMAT™

3

Easy separate feeding

- With roller tube adjustable between 40 and 50 mm above the trough,
- or FIXGRILL™ with spacings of 45 mm wide x 65 mm high.

4

Easy maintenance, durable, reliable

- A 10-year-warranty (*) on the augers. (*Degressive warranty)
- No corner wheels or parts susceptible to wear.
- Circuits can be winched up for easy, thorough cleaning.
- Optional daily winching provides better litter quality and less floor eggs.